



Experts in water.

DAVEY

APPLICATIONS

- Underground car parks
- Cellars
- Garages



SumpMaster Mini 2C Sump Pump Controller

Model Number: DSM-MINI-0.4

The SumpMaster Mini automatically controls two manual sump pumps, up to 400 watts each, to empty a sump or tank. It features a visual alarm, buzzer and BMS interface capability.

WHY CHOOSE THE Davey SumpMaster Mini 2C?

Provides fully automatic pump control and protection of two manual sump pumps up to 400 Watts each. Ideal with two Davey D40M sump pumps to pump clean or slightly dirty water.

Simple operation with an Auto / Off / Manual control switch.

Straightforward control via 3 floats, a low level float, start float and high level float.

Floats use 24VAC (extra low voltage) for added safety.

Lead pump is rotated on every start-up to equalise the hours of operation to maximise pump life.

Programmable lag pump delay from 10 seconds to 90 seconds. Factory set at 30 seconds.

Easy replacement of sump pumps as they plug directly into 240V 3-pin power sockets on the bottom of the control panel.

Provides high level, low level and no flow alarms.

All alarms will activate an alarm light, buzzer and a building management system (BMS) output.

ELECTRICAL DATA	
Controller Power Supply	240V, 50-60Hz (+/-2Hz)
IP Rating	IP43
Pump Power Supply	240V 50Hz
Visual Alarm	Flashing light with flash codes
Audible Alarm	Inbuilt 80dBa @ 1 metre
Operating Temperature	0° to 45°C, non-condensing

RANGE GUIDE/SUITABILITY		
Model	Suit Davey Models	Amps
DSM-MINI-0.4	D40M	3.7

